


## Tapered roller bearing 28158-28300X-TIMKEN - 28158-28300X-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/28158-28300x-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings					Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>02</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Inner	Outer
mm	mm	mm	N		N		N		
40.000	76.200	20.625	7500	1.45	19500	1.45	69000	28158	28300X
1.5748	2.9990	0.8129	18600		4300		15000		

Bearing Dimensions										Geometry Factors			Bearing Weights	
Shaft		Housing		Cage					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
Width B	Width C	ER. Dr. r <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>				A <sub>3</sub> <sup>(1)</sup>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm					
20.640	15.496	-4.8	1.5	45.6	47.5	1.5	71.0	68.0	2.3	1.1	20.7	12.5	0.0700	0.38
0.8244	0.6130	-0.19	0.06	1.77	1.87	0.06	2.80	2.68	0.09	0.05				0.05

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952312637
Inside diameter	40 mm
Outside diameter	76.2 mm
Thickness	20.625 mm
Weight	380 g
Packaging	1
Standard	No standard

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE