

Tapered roller bearing 46175-46368-TIMKEN - 46175-46368-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/46175-46368-timken>

TAPERED ROLLER BEARINGS

SINGLE-ROW • TYPE TS

TYPE TS

Bearing Dimensions								Part Number					
Load Ratings								Inner		Outer			
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁₀	Factor ⁽²⁾ K	Dynamic ⁽¹⁾ C ₉₀	Factor ⁽²⁾ K	Static C ₀						
mm	mm	mm	N		N		N						
in	in	in	lb		lb		lb						
44.450	93.662	31.750	129000	1.45	32000	1.45	150000						
1.7500	3.6875	1.2500	29100		7540		33500						
Bearing Dimensions													
Shaft								Housing					
Max Shaft				Backling				Shoulder Dia.					
Width B	Width C	ER. Co. μm	Fillet Radius r _s	Backling Shoulder Dia. d _s	Max Housing Fillet Radius r _h	Backling Shoulder Dia. D _s	Cage						
mm	mm	mm	mm	mm	mm	mm	A ₁₀ ⁽³⁾						
in	in	in	in	in	in	in	A ₁₁ ⁽³⁾						
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1						
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08						
								G ₁		G ₂			
								C ₀					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.9	0.8	54.8	3.3	87.0	2.1	1.1	44.4	13.6	0.0020		
1.2500	1.0313	-0.31	0.03	2.13	0.13	3.43	0.08	0.05					
31.750	26.196	-2.											

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952314020
Inside diameter	44.45 mm
Inside diameter	1 3/4" inch
Outside diameter	93.662 mm
Outside diameter	3 11/16" inch
Thickness	31.75 mm
Thickness	1 1/4" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE