



Tapered roller bearing 436-432X-TIMKEN - 436-432X-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/436-432x-timken>

TAPERED ROLLER BEARINGS														
SINGLE ROW • TYPE TS														
TYPE TS														
														
Bearing Dimensions				Load Ratings						Part Number				
Bore d	O.D. D	Width B		Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ e	Static C ₃		Inner	Outer			
mm	mm	mm		N		N		N						
in	in	in		lb		lb		lb						
46.037	95.250	31.753		127000	0.20	32000	10000	2.05	140000	436	432X			
1.8125	3.7500	1.2501		28500		7400	3000		32400					
Bearing Dimensions														
Shaft ³⁾				Housing				Cage		Geometry Factors			Bearing Weight	
Width B	Width C	ER. Co. μm	Max Shaft Fillet Radius R _{fs}	Backling Shoulder Dia. d ₁	Backling Shoulder Dia. d ₂	Max Housing Fillet Radius r ₁	Backling Shoulder Dia. D ₁	A ₁ ⁽³⁾	A ₂ ⁽³⁾	G ₁	G ₂	C ₃	kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				lb	
in	in	in	in	in	in	in	in	in	in				oz	
25.000	25.195	-0.1	3.5	52.0	58.0	3.3	87.0	81.0	1.6	0.5	42.5	11.3	0.005	0.09
1.1772	1.0213	-0.36	0.14	2.05	2.32	0.13	3.43	3.19	0.06	0.02				2.18

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952315041
Inside diameter	46.037 mm
Outside diameter	95.25 mm
Thickness	31.753 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE