


## Tapered roller bearing 6575-6535-TIMKEN - 6575-6535-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/6575-6535-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings					Part Number		
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
76.200	161.925	53.975	42000	1.52	114000	20900	1.46	523000	6575	6535
3.0000	6.3750	2.1250	98000		29000	13900		118000		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>					G <sub>1</sub>	
53.975	42.862	-13.2	0.4	102.6	104.6	3.3	104.8	101.8	4.1	8.8	108.6	33.5	0.1027	5.40
2.1250	1.6875	-0.52	0.25	3.82	4.09	0.13	9.39	5.59	0.16	0.04				11.91

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952321745
Inside diameter	76.2 mm
Inside diameter	3" inch
Outside diameter	161.925 mm
Outside diameter	6 3/8" inch
Thickness	53.975 mm
Thickness	2 1/8" inch
Weight	5400 g
Packaging	1
Standard	No standard

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE