


## Tapered roller bearing 95500-95925-TIMKEN - 95500-95925-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/95500-95925-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N	N	N			
127.000	234.950	63.500	42900	1.02	103000	193000	1.58	95500	95925	
5.0000	9.2500	2.5000	141000		36700	22000				

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sub>f1</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(2)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(3)</sup>	A <sub>3</sub> <sup>(3)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
63.500	49.212	-14.6	0.4	142.0	154.6	3.3	217.0	200.0	6.4	3.8	453.9	50.4	0.1023	15.74
2.5000	1.9275	-0.35	0.25	5.50	6.06	0.13	9.94	8.23	0.25	0.15				25.68

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952325149
Inside diameter	127 mm
Outside diameter	234.95 mm
Thickness	63.5 mm
Weight	11740 g
Packaging	1
Standard	No standard

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE