


Tapered roller bearing EE128110-128160-TIMKEN - EE128110-128160-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/ee128110-128160-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|--|---------------------------------------|-----------------------|--------|-------------|--------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₀₂ | Factor ⁽²⁾ C ₀₂ | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | N | N | | | |
| 280.192 | 406.400 | 69.850 | 32400 | 0.30 | 24000 | 15000 | 1.51 | 182000 | EE128110 | 128160 |
| 11.2012 | 16.0000 | 2.7569 | 20600 | | 5300 | 3500 | | 42000 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|--------|---------|------|--|---------------------------------------|--|---------------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|-------|
| Width | | ER. Dr. | | Shaft | | Housing | | Cage | | G ₁ | G ₂ | C ₃ | | |
| B | C | mm | mm | Max Shaft Fillet Radius R ₁ | Backling Shoulder Dia. d _s | Max Housing Fillet Radius r ₁ | Backling Shoulder Dia. D _s | A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | | | | mm | mm |
| 67.629 | 53.975 | 6.6 | 6.8 | 307.0 | 306.6 | 3.3 | 384.0 | 336.0 | 6.8 | 1.5 | 1727.7 | 252.2 | 0.1628 | 27.97 |
| 2.6943 | 2.1250 | 0.26 | 0.27 | 12.09 | 12.17 | 0.13 | 15.12 | 14.88 | 0.27 | 0.08 | | | | 81.87 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | TIMKEN |
| N° Ean13 | 3663952329048 |
| Inside diameter | 280.192 mm |
| Outside diameter | 406.4 mm |
| Thickness | 69.85 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE