


Deep groove ball bearing single row ZKLN60110-2Z-INA - ZKLN60110-2Z-INA


<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/zkln60110-2z-ina>

Axial angular contact ball bearings ZKLN60110-2Z
double direction, gap seals on both sides



d	60 mm	Tolerance: -0.008
D	110 mm	Tolerance: -0.015
B	45 mm	Tolerance: -0.25
α	60 °	Contact angle
D_{g, max}	100 mm	
d₁	85 mm	
d_{2, max}	82 mm	
r_{1, max}	0.6 mm	
r_{2, max}	0.6 mm	
m	2.2 kg	Mass
C_d	84000 N	Basic dynamic load rating, axial
C_{0d}	214000 N	Basic static load rating, axial
n_{lim}	3500 1/min	Limiting speed for grease lubrication
M_{0d}	6 Nm	Bearing frictional torque
S_{0d}	1300 N/mm	Axial rigidity
C_{0d}	1500 N/mmrad	Tilting rigidity
M_{0d}	13.7 kg x cm ²	Mass moment of inertia for rotating inner ring
	3 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZMA6098	Designation of recommended INA locknut
	AM60	Designation of recommended INA locknut
		Locknuts not included in delivery.
M₀	100 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	17893 N	Axial preload force

Design of adjacent construction



PRODUCT FEATURES

Brand	INA
N° Ean13	3663952334967
Inside diameter	60 mm
Inside diameter	2.362" inch
Sealing	Shield on both sides
Outside diameter	110 mm
Outside diameter	4.331" inch
Thickness	45 mm
Thickness	1.772" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE