


Tapered roller bearing 3387-3320-B-TIMKEN - 3387-3320-B-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/3387-3320-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF



| Bearing Dimensions | | | | Load Ratings | | | | | | Part Number | |
|--------------------|--------|---------|---------------------------------------|--------------------------|------|---------------------------------------|--------------------------|-----------------------|-------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Y | Dynamic ⁽¹⁾ C ₂ | Factors ⁽²⁾ K | Static C ₃ | Inner | Outer | |
| mm | mm | mm | N | | | N | | N | | | |
| 38.130 | 80.167 | 10.320 | 115000 | 0.27 | 1.24 | 22000 | 13000 | 120000 | 3387 | 3320-B | |
| 1.500 | 3.182 | 0.408 | 25000 | | | 6700 | 3100 | 25100 | | | |

| Bearing Dimensions | | | | | | Shaft | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|---------|----------------------------|---------------------------------|-----------------------------|--|--------------------------------------|--------------------------------------|--------------------------------------|----------------|----------------|------------------|--|------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽³⁾ | Outer Ring Range D ₁ | Flange Width C ₂ | Max Shaft Fillet Radius R ⁽⁴⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. d ₂ | Sealing Shoulder Dia. D ₁ | G ₁ | G ₂ | C ₃ | | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | | lb | |
| 38.301 | 23.812 | -18.0 | 84.826 | 4.762 | 0.8 | 46.5 | 46.8 | 77.8 | 24.8 | 12.1 | 0.0144 | | 0.75 | |
| 1.508 | 0.937 | -0.43 | 3.336 | 0.1875 | | 1.75 | 1.77 | 3.03 | | | | | 1.63 | |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | TIMKEN |
| N° Ean13 | 3663952336497 |
| Inside diameter | 38.1 mm |
| Inside diameter | 1 1/2" inch |
| Outside diameter | 80.167 mm |
| Outside diameter | 3 5/32" inch |
| Thickness | 10.32 mm |
| Thickness | 13/32" inch |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE