


Tapered roller bearing JP6049-JP6010-B-TIMKEN - JP6049-JP6010-B-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/jp6049-jp6010-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF



Bearing Dimensions				Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C1	Factors ⁽²⁾ e	Dynamic ⁽¹⁾ C2	Factors ⁽²⁾ K	Static C0	Inner	Outer		
mm	mm	mm	N		N		N				
60	100	20	8200	0.45	21400	17200	101000	JP6049	JP6010-B		
2.362	3.937	0.787	18500		4810	3860	22800				

Bearing Dimensions						Shaft			Housing		Geometry Factors			Bearing Weight
Width B	Width C	Eff. Ctr. a ⁽¹⁾	Outer Ring Range D1	Flange Width C2	Max Shaft Fillet Radius (R ⁽¹⁾)	Sealing Shoulder Dia. d1	Sealing Shoulder Dia. d2	Sealing Shoulder Dia. D1	D1	D2	C1	C2	kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
20	15	1.3	100-200	2.00	2.5	66.0	69.0	66.0	29.5	22.5	0.0022	0.0022	0.60	
0.787	0.610	0.05	4.133	0.118	0.08	2.60	2.72	2.60	3.98				1.37	

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3616060457080
Inside diameter	60 mm
Inside diameter	2.362" inch
Outside diameter	100 mm
Outside diameter	3.937" inch
Thickness	20 mm
Thickness	0.787" inch
Weight	600 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE