



## Drawn cup roller bearing TAM810-IKO - TAM810-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/tam810-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**

Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
<b>B</b>	---	---	<b>TAM 810</b>	7.1	---	---	---	---	---	---

Boundary dimensions mm		Standard reporting dimensions mm						Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring		
F <sub>w</sub>	D	C	t <sub>2</sub> Max.	Shaft dia. H7 Max.	H7 Min.	Housing bore dia. N7 Max.	N7 Min.	N	N	rpm	---		
8	15	10	1.3	8.000	7.991	15.010	14.992	---	---	3 470	2 880	45 000	---

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952351933
Inside diameter	8 mm
Outside diameter	15 mm
Thickness	10 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE