

Tapered roller bearing 32930-TIMKEN - 32930-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32930-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • IsoClass

IsoClass

Bearing Dimensions			Load Ratings					Part Number	
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽³⁾ C ₂	Factor ⁽³⁾ K	Static C ₀	Assembly Inner/Outer	Part Number
mm	mm	mm	N		N		N		
in	in	in	lbf		lbf		lbf		
150.000	210.000	38.000	524000	0.33	849000	47200	1.78	573000	22930
5.9055	8.2677	1.4961	128500		189300	10600		129000	

Mounting Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER Co. g ⁽⁴⁾	Max Shaft Fillet Radius R ⁽⁵⁾	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ⁽⁶⁾	Backing Shoulder Dia. D _s	Backing Shoulder Dia. D ₂	A ₁ ⁽⁷⁾	A ₂ ⁽⁸⁾	G ₁	G ₂	C ₃	kg	
mm	mm	in	mm	mm	mm	mm	mm	mm	mm	in	in	in	lb	
38.000	36.000	-1.5	2.5	160.0	160.0	2.0	200.0	197.0	1.5	2.0	428.9	151.2	0.1167	3.89
1.4961	1.4173	-0.06	0.10	6.30	6.30	0.08	7.87	7.75	0.06	0.08	16.84	5.95	0.0046	0.86

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952354040
Inside diameter	150 mm
Outside diameter	210 mm
Thickness	38 mm
Weight	4000 g
Packaging	-
Standard	-

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE