

## Tapered roller bearing 32030X-TIMKEN - 32030X-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32030x-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings					Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(4)</sup> K	Static C <sub>0</sub>	Assembly Inner/Outer	Part Number
mm	mm	mm	N		N		N		
150.000	225.000	48.000	44000	0.84	11000	1.27	73000		32030K
5.900	8.850	1.888	9950		2300		16000		

  

Geometric Dimensions										Geometry Factors		Bearing Weight		
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Backing Fillet Radius r <sup>(3)</sup>	Max Housing Fillet Radius R <sup>(4)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Cage A <sub>1</sub> <sup>(5)</sup>	Cage A <sub>2</sub> <sup>(6)</sup>	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>	kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	g
48.000	36.000	1.0	3.0	163.0	100.0	2.5	217.0	206.0	2.0	4.0	407.0	114.0	0.1014	6.30
1.888	1.473	0.04	0.13	6.42	6.80	0.10	8.54	8.11	0.11	0.16				14.08

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952354057
Inside diameter	150 mm
Outside diameter	225 mm
Thickness	48 mm
Weight	6380 g
Packaging	1
Standard	No standard

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE