

## Tapered roller bearing 32940-TIMKEN - 32940-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32940-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(4)</sup> K	Static C <sub>0</sub>	Assembly	Inner/Outer	
mm	mm	mm	N		N	N	N			
in	in	in	lbf		lbf	lbf	lbf			
200.000	280.000	51.000	501000	4.25	140000	18300	1.48	1050000	32940	
7.8740	11.0236	2.0079	126000		32700	22100		250000		

  

Mounting Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(3)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(4)</sup>	A <sub>2</sub> <sup>(5)</sup>				G <sub>1</sub>	
mm	mm	in	mm	mm	mm	mm	mm	mm	mm	in	in	in	in	lb
51.000	26.000	3.0	3.0	213.0	213.0	2.5	212.0	262.0	4.6	1.6	0.03	0.029	0.029	3.45
2.0079	1.0234	0.12	0.12	8.39	8.34	0.10	8.371	10.31	0.18	0.063				0.076

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952354125
Inside diameter	200 mm
Outside diameter	280 mm
Thickness	51 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE