

## Tapered roller bearing 32956-TIMKEN - 32956-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32956-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings					Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Assembly Inner/Outer	
mm	mm	mm	N		N	N	N		
in	in	in	lbf		lbf	lbf	lbf		
280.000	380.000	63.500	850000	0.43	220000	102000	1700000	32956	
11.0236	14.9608	2.5000	191000		49000	26700	4010000		

  

Mounting Dimensions										Geometry Factors			Bearing Weight
Shaft					Housing					Cage			
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(3)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(4)</sup>	A <sub>2</sub> <sup>(5)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>	kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	lbm
in	in	in	in	in	in	in	in	in	in	in	in	in	oz
63.500	40.000	11.4	3.0	290.0	300.0	2.5	300.0	290.0	7.5	3.4			10.8
2.5000	1.5748	0.45	0.12	11.61	11.81	0.10	14.49	14.52	0.29	0.14			42.69

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952354194
Inside diameter	280 mm
Outside diameter	380 mm
Thickness	63.5 mm
Packaging	1
Standard	No standard

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE