

## Tapered roller bearing 32968-TIMKEN - 32968-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32968-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(3)</sup> K	Static C <sub>0</sub>	Assembly Inner/Outer		
mm	mm	mm	N		N	N	N			
in	in	in	lbf		lbf	lbf	lbf			
340.000	460.000	76.000	1220000	0.04	216000	22700	1.34	204000	32968	
13.398	18.112	2.992	274000		71000	5230		594000		

  

Mounting Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>4</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>2</sub>	Backing Shoulder Dia. D <sub>3</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>				G <sub>1</sub>	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	lbs
34.000	57.000	14.7	4.0	300.0	30.0	3.0	460.0	402.0	16.5	4.0	2703.6	309.5	0.1967	24.40
2.992	2.244	0.58	0.16	14.13	14.32	0.12	17.98	15.81	0.61	0.17				75.56

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952354224
Inside diameter	340 mm
Outside diameter	460 mm
Thickness	76 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE