

## Tapered roller bearing 395-S-394D-TIMKEN - 395-S-394D-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/395-s-394d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup>		Static <sup>(2)</sup>		Dynamic <sup>(3)</sup>		Factor <sup>(4)</sup>	
mm	mm	mm	mm	C <sub>10</sub>	N	C <sub>0</sub>	N	C <sub>90</sub>	N	C <sub>50</sub>	K
66.675	110.000	52.388	46.838	32000	17000	0.40	1.88	2.50	25600	17800	1.45
2.6250	4.3267	2.0625	1.8125	38700	19700				5700	3970	

  

Part Number		Dimensions						Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>		kg	
395-S	394D	3.5 0.14	76.0 3.11	8.8 0.35	106.4 4.11	-	-	50.0	21.4	0.0984		1.26 3.88	

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952357164
Inside diameter	66.675 mm
Outside diameter	110 mm
Thickness	52.388 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE