


Drawn cup roller bearing YB66-IKO - YB66-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/yb66-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
9.525 ($\frac{3}{8}$)	—	—	—	—	YB 66	5.3	—	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic	Basic static	Allowable	Assembled	
F_w	D	C	b_2	Shaft dia. h_8	Housing bore dia. J_7	C	load rating C_0	load rating C_0	rotational speed ^(*)	inner ring	
mm	mm	mm	mm	Max.	Min.	Max.	Min.	N	N	rpm	
9.525	14.288	9.525	—	9.525	9.516	14.298	14.280	6 920	9 410	16 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952361246
Inside diameter	9.525 mm
Outside diameter	14.288 mm
Thickness	9.52 mm
Weight	18 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE