

Drawn cup roller bearing BHAM1212-IKO - BHAM1212-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bham1212-iko>

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series

Identification number										
Shaft dia. mm (inch)	Standard			Closed end			BHAM 1212			
	Mass (Ref.) g			Mass (Ref.) g			Mass (Ref.) g	Grease retained Mass (Ref.) g	Mass (Ref.) g	
19.050 (3/4)	—	—	—	—	—	—	28.5	—	—	
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ N	Assembled inner ring rpm	
F _w	D	C	Shaft dia. H7 Max.	Housing bore dia. H7 Max.	Min.					
19.050 (3/4)	26.988 (1 1/8)	19.05 (3/4)	1.3	19.050	19.037	27.000	26.979	16 600	22 600	20 000
IRB 812-1										

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952361819
Inside diameter	19.05 mm
Outside diameter	26.988 mm
Thickness	19.05 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE