

Drawn cup roller bearing YB124-IKO - YB124-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/yb124-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number			Identification number			Grease retained Mass (Ref.) g	Mass (Ref.) g			
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end					
19.050 ($\frac{3}{4}$)	—	—	—	—	—	—	YB 124	8.5			
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating C ₀	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
F _w	D	C	h ₆ Max.	h ₆ Min.	J7 Max.	J7 Min.	N				
19.050	25.400	6.35	19.050	19.037	25.412	25.391	7 820	10 200	8 000	—	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952361826
Inside diameter	19.05 mm
Outside diameter	25.4 mm
Thickness	6.35 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE