


Drawn cup roller bearing YB1412-IKO - YB1412-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/yb1412-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
22.225 ($\frac{7}{8}$)	—	—	—	—	—	—	—	—	—	—	—	—	—
												YB 1412	31

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F _w	D	C	Shaft dia. h6	Housing bore dia. J7	Max.	Min.				
22.225	28.575	19.05	22.225	22.212	28.587	28.566	26 300	50 700	7 000	IRB 1012

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060457448
Inside diameter	22.225 mm
Outside diameter	28.587 mm
Thickness	19.05 mm
Weight	31 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE