


## Drawn cup roller bearing BHAM2020-IKO - BHAM2020-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bham2020-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g																																			
	Standard	Mass (Ref.) g	Closed end																																													
31.750 (1 1/4)	---	---	---	---	---	---	---	---	---	---	---	---	---																																			
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions mm(inch)</th> <th colspan="4">Standard mounting dimensions mm</th> <th>Basic dynam. load rating</th> <th>Basic static load rating</th> <th>Allowable rotational speed<sup>(*)</sup></th> <th>Assembled inner ring</th> </tr> <tr> <th>F<sub>w</sub></th> <th>D</th> <th>C<sub>0</sub></th> <th>Shaft dia. h8</th> <th>Housing bore dia. J7</th> <th>Max.</th> <th>Min.</th> <th>C</th> <th>N</th> <th>N</th> <th>rpm</th> <th>IRB 1620</th> </tr> </thead> <tbody> <tr> <td>31.750 (1 1/4)</td> <td>41.275 (1 1/2)</td> <td>31.75 (1.250)</td> <td>3.4</td> <td>31.750</td> <td>31.734</td> <td>41.289</td> <td>41.264</td> <td>40 000</td> <td>69 600</td> <td>12 000</td> <td>IRB 1620</td> </tr> </tbody> </table>														Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynam. load rating	Basic static load rating	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring	F <sub>w</sub>	D	C <sub>0</sub>	Shaft dia. h8	Housing bore dia. J7	Max.	Min.	C	N	N	rpm	IRB 1620	31.750 (1 1/4)	41.275 (1 1/2)	31.75 (1.250)	3.4	31.750	31.734	41.289	41.264	40 000	69 600	12 000	IRB 1620
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynam. load rating	Basic static load rating	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring																																						
F <sub>w</sub>	D	C <sub>0</sub>	Shaft dia. h8	Housing bore dia. J7	Max.	Min.	C	N	N	rpm	IRB 1620																																					
31.750 (1 1/4)	41.275 (1 1/2)	31.75 (1.250)	3.4	31.750	31.734	41.289	41.264	40 000	69 600	12 000	IRB 1620																																					

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952362335
Inside diameter	31.75 mm
Outside diameter	41.275 mm
Thickness	31.75 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE