


Drawn cup roller bearing BAM228-IKO - BAM228-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam228-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g																																	
	Standard	Mass (Ref.) g	Closed end																																											
34.925 (1 3/8)	---	---	---	---	---	---	---	---	---	---	---	---	---																																	
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="4">Standard mounting dimensions</th> <th>Basic dynam.</th> <th>Basic static</th> <th>Allowable</th> <th>Assembled</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th>Shaft dia. mm</th> <th>Housing bore dia. mm</th> <th>Max.</th> <th>Min.</th> <th>load rating C</th> <th>load rating C_0</th> <th>rotational speed(*) rpm</th> <th>inner ring</th> </tr> </thead> <tbody> <tr> <td>34.925</td> <td>41.275</td> <td>12.70</td> <td>34.925</td> <td>34.909</td> <td>41.289</td> <td>41.264</td> <td>9 770</td> <td>16 600</td> <td>10 000</td> <td>IRB 188</td> </tr> </tbody> </table>														Boundary dimensions			Standard mounting dimensions				Basic dynam.	Basic static	Allowable	Assembled	F_w	D	C	Shaft dia. mm	Housing bore dia. mm	Max.	Min.	load rating C	load rating C_0	rotational speed(*) rpm	inner ring	34.925	41.275	12.70	34.925	34.909	41.289	41.264	9 770	16 600	10 000	IRB 188
Boundary dimensions			Standard mounting dimensions				Basic dynam.	Basic static	Allowable	Assembled																																				
F_w	D	C	Shaft dia. mm	Housing bore dia. mm	Max.	Min.	load rating C	load rating C_0	rotational speed(*) rpm	inner ring																																				
34.925	41.275	12.70	34.925	34.909	41.289	41.264	9 770	16 600	10 000	IRB 188																																				

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952363035
Inside diameter	34.925 mm
Outside diameter	41.275 mm
Thickness	12.7 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE