


# Tapered roller bearing EE161403D-161900-TIMKEN - EE161403D-161900-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/ee161403d-161900-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDI

**TYPE TDI**



Bearing Dimensions				Load Ratings									
Bore d	O.D. D	Width T	Double Inner Ring Width B	Dynamic <sup>CR</sup> C <sub>10</sub>	Static <sup>CR</sup> C <sub>0</sub>	Factor <sup>CR</sup> Y <sub>1</sub>	Factor <sup>CR</sup> Y <sub>2</sub>	Dynamic <sup>CR</sup> C <sub>90</sub>	Dynamic <sup>CR</sup> C <sub>50</sub>	Dynamic <sup>CR</sup> C <sub>100</sub>	Factor <sup>CR</sup> K		
mm	mm	mm	mm	N	N	N	N	N	N	N			
356.387	482.600	104.775	101.600	90400	142000	0.5	1.4	2.0	142000	122000	247000	1.17	
14.0310	19.0000	4.1200	4.0000	314200				31900	27400	55000			

Part Number		Dimensions				Geometry Factors			Bearing Weight
Inner	Outer	Max Shaft Fillet Radius r <sub>s</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sub>h</sub>	Backing Shoulder Dia. D <sub>s</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>	kg
mm	mm	mm	mm	mm	mm				lbm
EE161403D	161900	1.5	378.0	6.6	493.0	1726.0	209.0	0.1361	48.00
		0.08	14.75	0.25	17.75				107.11

## PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952370798
Inside diameter	356.387 mm
Outside diameter	482.6 mm
Thickness	104.775 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE