

Thrust roller bearing T15500-TIMKEN - T15500-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/thrust/t15500-timken>

| TAPERED ROLLER BEARINGS | | | | | | | | | | |
|-------------------------|-----------|--------------------|--------------------|------------------|-----------------------|---------------------------------------|-----------------------|-----------------|-------------------------|--|
| THRUST - TYPE TTHDFL | | | | | | | | | | |
| TYPE TTHDFL | | | | | | | | | | |
| | | | | | | | | | | |
| Part Number | | Dimensions | | | Ratings | | | Bearing Weight | | |
| Bearing | Cage Type | Bore d | Outside Diameter D | Width T | Shaft Fillet Radius R | Housing Fillet Radius ¹⁾ r | Static C ₀ | | Dynamic C ₁₀ | |
| | | mm in. | mm in. | mm in. | mm in. | mm in. | N lbf | N lbf | kg lbs. | |
| T15500 | Machined | 393.700 15.5000 | 495.300 19.5000 | 44.450 1.7500 | 3.3 0.13 | 3.3 0.13 | 6900000 1550000 | 373000 83700 | * | |

¹⁾These maximum fillet radii will be obtained by the bearing centers.
²⁾Contact your Timken engineer for details.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | TIMKEN |
| N° Ean13 | 3663952375908 |
| Inside diameter | 393.7 mm |
| Outside diameter | 495.3 mm |
| Thickness | 44.45 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE