


## Needle roller bearing GBRI243720-IKO - GBRI243720-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/gbri243720-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F<sub>w</sub></i>
<b>38.100</b> (1 1/2)	<b>GBRI 243720</b>	335	38.100 (1 1/2)	58.738 (2 5/16)	31.750 (1 1/2)	32.000	44.450 (1 3/4)

Standard mounting dimensions mm		Ball diam. mm <i>C</i>	Ball rate mm <i>C<sub>0</sub></i>	Allowable rotational speed (°) rpm	Assembled inner ring <b>LRBZ 242820</b>
<i>d<sub>s</sub></i> Min.	<i>D<sub>s</sub></i> Max.				
43.3	43.4	53.7	0.6	69 700	141 000

Notes: (°) Maximum permissible corner radius of the housing.  
(°) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-packed. Perform proper lubrication.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952377506
Inside diameter	38.1 mm
Inside diameter	1 1/2" inch
Outside diameter	58.738 mm
Outside diameter	2 5/16" inch
Thickness	32 mm
Thickness	1.26" inch
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE