


Needle roller bearing GBRI264116-IKO - GBRI264116-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/gbri264116-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
41.275 (1 5/8)	GBRI 264116	350	41.275 (1 5/8)	65.088 (2 5/8)	25.400 (1)	25.650	50.800 (2)

Standard mounting dimensions mm				Basic dynamic load rating C ₀ N	Static load rating C ₀ N	Allowable rotational speed (°) rpm	Assembled inner ring LRBZ 263216
d _a Min.	d _a Max.	D _a Max.	r _{as max} (°)				
48	49	59.2	1	63 100	130 000	3 000	

Notes: (°) Maximum permissible corner radius of the housing.
(°) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952377537
Inside diameter	41.275 mm
Outside diameter	65.088 mm
Thickness	25.65 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE