


## Needle roller bearing GBR364828-IKO - GBR364828-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/gbr364828-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm <sup>(1)</sup>	
			F <sub>e</sub>	D	C	D <sub>s</sub> Max.	r <sub>as max</sub>
<b>57.150</b> (2 1/4)	<b>GBR 364828</b>	580	57.150 (3)	76.200 (3)	44.450 (1 3/4)	69.2	1.5
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>					
N	N	rpm					
133 000	276 000	2 500					

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 2. The outer ring has an oil groove and an oil hole.  
3. No grease is pre-applied. Perform proper lubrication.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952377568
Inside diameter	57.15 mm
Outside diameter	76.2 mm
Thickness	44.45 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE