


Needle roller bearing GBR445624-IKO - GBR445624-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/gbr445624-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F _o	D	C	D _s Max.	r _{as} max
69.850 (2 3/4)	GBR 445624	585	69.850 ⁽²⁾	88.900 ⁽²⁾	38.100 ⁽²⁾	82	1.5
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽³⁾					
N	N	rpm					
125 000	273 000	2 000					

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952377599
Inside diameter	69.85 mm
Outside diameter	88.9 mm
Thickness	38.1 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE