


Needle roller bearing GBR162416-IKO - GBR162416-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/gbr162416-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (1)	
			F	D	C	D _s Max.	r _{as max}
25.400 (1)	GBR 162416	106	25.400 (1)	38.100 (1 1/2)	25.400 (1)	33.3	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed(2)					
N	N	rpm					
41 400	67 100	6 000					

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952377742
Inside diameter	25.4 mm
Inside diameter	1" inch
Outside diameter	38.1 mm
Outside diameter	1 1/2" inch
Thickness	25.4 mm
Thickness	1" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE