


Needle roller bearing GBR182616-IKO - GBR182616-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/gbr182616-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F	D	C	D _s Max.	r _{as} max
28.575 (1 1/8)	GBR 182616	117	28.575(1 1/8)	41.275(1 1/2)	25.400(1)	36.3	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
N	N	rpm					
43 900	75 300	5 500					

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952377759
Inside diameter	28.575 mm
Outside diameter	41.275 mm
Thickness	25.4 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE