


Needle roller bearing GBRI446832-IKO - GBRI446832-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/gbri446832-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F_w</i>
69.850 (2 3/4)	GBRI 446832	1 840	69.850 (2 3/4)	107.950 (4 1/4)	50.800 (2)	51.050	82.550 (3 1/4)

Standard mounting dimensions mm		Basic dynamic load (C _r) N	Limiting load rating C _u N	Allowable rotational speed (F) rpm	Assembled inner ring
<i>d_a</i> Min.	<i>D_a</i> Max.				
77	79	214 000	452 000	1 800	LRBZ 445232

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952377964
Inside diameter	69.85 mm
Outside diameter	107.95 mm
Thickness	50.8 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE