

Needle roller bearing RNA49-22-U-IKO - RNA49-22-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rna49-22-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
28	—	RNA 49/22U	—	—	55.5	28	39	17	0.3

Standard rounding dimension D_s Max. mm	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (2)
37	18 300	23 700	7 000

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952378985
Inside diameter	28 mm
Outside diameter	39 mm
Thickness	17 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE