


Needle roller bearing RNA4905-U-IKO - RNA4905-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rna4905-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
30	—	RNA 4905U	—	—	83	30	42	17	0.3
Standard mounting diameter D_s Max. mm	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed (2) rpm						
40	20 300	25 100	6 500						

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379029
Inside diameter	30 mm
Inside diameter	1.181" inch
Outside diameter	42 mm
Outside diameter	1.654" inch
Thickness	17 mm
Thickness	0.669" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE