

Needle roller bearing RNA49-32-U-IKO - RNA49-32-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rna49-32-u-iko>

IKO

MACHINED TYPE NEEDLE ROLLER BEARINGS

With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_1 (1)
40	---	RNA 49/32U	---	---	94.5	40	52	20	0.6
Standard mounting dimension D_s Max. mm									
	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed (1) rpm						
48	29 400	44 200	5 000						

Notes: (1) Minimum allowable value of chamfer dimension r .
 Allowable rotational speed applies to grease lubrication.
 The outer ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379142
Inside diameter	40 mm
Inside diameter	1.575" inch
Outside diameter	52 mm
Outside diameter	2.047" inch
Thickness	20 mm
Thickness	0.787" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE