

Needle roller bearing RNA49-42-U-IKO - RNA49-42-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rna49-42-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|---|-----------------------|-------------------|----------------|---------------|---------------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_a (1) |
| 50 | — | RNA 49/42U | — | — | 173 | 50 | 65 | 22 | 0.6 |
| Standard rounding dimension D_s Max. mm | N | N | N | rpm | | | | | |
| Basic dynamic load rating C | 38 000 | 60 900 | 4 000 | | | | | | |
| Basic static load rating C_0 | | | | | | | | | |
| Allowable rotational speed (reference speed) | | | | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952379272 |
| Inside diameter | 50 mm |
| Outside diameter | 65 mm |
| Thickness | 22 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE