

Needle roller bearing RNA6911-U-IKO - RNA6911-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rna6911-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F _w	D	C	r _s (1)
63	—	—	—	RNA 6911U	470	63	80	45	1
Standard mounting diameter D _s Max. mm	N	N	N	Allowable (2) (3)					
Basic dynamic load rating C	89 400	171 000	3 000						
Basic static load rating C ₀									
Allowable speed (2)									

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379432
Inside diameter	63 mm
Outside diameter	80 mm
Thickness	45 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE