

Needle roller bearing RNA49-58-UU-IKO - RNA49-58-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rna49-58-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref) g | Boundary dimensions mm | | |
|--|---------------------------------------|--|--|---------------|--------------------|---------------------------|-----|--------------------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C ⁽¹⁾ |
| 65 | RNA 49/58UU | — | — | — | 275 | 65 | 82 | 25 1 |
| Standard mounting diameter D_A Max. mm | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed ⁽²⁾ rpm | | | | | |
| 77 | 53 400 | 89 200 | 3 000 | | | | | |

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension r .
⁽²⁾ Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952379456 |
| Inside diameter | 65 mm |
| Outside diameter | 82 mm |
| Thickness | 25 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE