

## Needle roller bearing RNA6912-U-IKO - RNA6912-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rna6912-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm		
	With two seals	With one seal	With two seals	With one seal		F <sub>w</sub>	D	C <sup>(1)</sup> r <sub>s</sub> mm
<b>68</b>	—	—	—	<b>RNA 6912U</b>	505	68	85	45   1
Standard mounting diameter D <sub>s</sub> Max. mm	N	N	N	Allowable rotational speed <sup>(2)</sup>				
	93 400	186 000	3 000					

Notes: <sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379494
Inside diameter	68 mm
Outside diameter	85 mm
Thickness	45 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE