


## Needle roller bearing RNA49-62-UU-IKO - RNA49-62-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rna49-62-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F <sub>w</sub>	D	C	r <sub>s</sub> (1)
70	<b>RNA 49/62UU</b>	—	—	—	320	70	88	25	1
Standard mounting diameter D <sub>s</sub> Max. mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed (2)						
83	55 700	96 300	2 500 rpm						

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379517
Inside diameter	70 mm
Outside diameter	88 mm
Thickness	25 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE