


## Needle roller bearing RNA6914-UU-IKO - RNA6914-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rna6914-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm		
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$ <sup>(1)</sup>
80	—	—	<b>RNA6914UU</b>	—	910	80	100	54   1

Standard mounting diameter $D_s$ Max. mm	Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(2)</sup> rpm
95	124 000	281 000	2 500

Notes: <sup>(1)</sup> Minimum allowable value of chamfer dimension  $r$ .  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379623
Inside diameter	80 mm
Outside diameter	100 mm
Thickness	54 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE