

Needle roller bearing RNA4924-UU-IKO - RNA4924-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rna4924-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F _w	D	C	r _s (1)
135	RNA 4924UU	—	—	—	1 940	135	165	45	1.1
Standard mounting diameter D _s Max. mm	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed (2)						
158.5	178 000	410 000	1 400						

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379906
Inside diameter	135 mm
Inside diameter	5.315" inch
Outside diameter	165 mm
Outside diameter	6.496" inch
Thickness	45 mm
Thickness	1.772" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE