

Needle roller bearing RNA4926-UU-IKO - RNA4926-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rna4926-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r (1)
150	RNA 4926UU	—	—	—	2 360	150	180	50	1.5
Standard mounting dimension D_A Max. mm	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (1)						
172	206 000	511 000	1 300						

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379913
Inside diameter	150 mm
Outside diameter	180 mm
Thickness	50 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE