


Needle roller bearing RNA4928-U-IKO - RNA4928-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rna4928-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_a (1)
160	—	RNA 4928U	—	—	2 510	160	190	50	1.5
Standard rounding dimension D_s Max. mm									
	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (reference)						
182	N	N	rpm						
	214 000	549 000	1 200						

Notes: (1) Minimum allowable value of chamfer dimension r .
 Allowable rotational speed applies to grease lubrication.
 Remarks: 1. The outer ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379937
Inside diameter	160 mm
Outside diameter	190 mm
Thickness	50 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE