

## Needle roller bearing NA6901-U-IKO - NA6901-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na6901-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
<b>12</b>	—	—	—	—	<b>NA 6901U</b>	45.5	12	24	22	23

$r_s$ min ( <sup>1)</sup> )	$F_w$	Standard mounting dimensions mm			Basic static load rating $C_0$ N	Allowable rotational speed( <sup>2)</sup> ) rpm	Assembled inner ring LRTZ 121623
		Min.	Max.	$d_s$			
0.3	16	14	15	22	15 500	20 400	12 000

Note(<sup>1</sup>) Minimum allowable value of diameter dimension  $r$   
 Note(<sup>2</sup>) Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381107
Inside diameter	12 mm
Outside diameter	24 mm
Thickness	23 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE