


Needle roller bearing NA6906-U-IKO - NA6906-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na6906-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
30	—	—	—	NA 6906U	185	30	47	30	31

r_s min (1)	F_w	Standard mounting dimensions mm			Basic static load rating C_0 N	Allowable rotational speed(2) rpm	Assembled inner ring
		Min.	Max.	Max.			
0.3	35	32	34	45	40 100	63 000	5 500

Note(1) Minimum allowable value of diameter dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381398
Inside diameter	30 mm
Outside diameter	47 mm
Thickness	31 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE