

Needle roller bearing NA69-32-U-IKO - NA69-32-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na69-32-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
32	—	—	—	—	NA 69/32U	300	32	52	36	37

r_s min (1)	F_w	Standard mounting dimensions mm		D_a Max.	Basic static load rating C_0 N	Basic dynamic load rating C_1 N	Allowable rotational speed(2) rpm	Assembled inner ring
		Min.	Max.					
0.6	40	36	39	48	50 300	88 300	5 000	LRTZ 324037

Note(1) Minimum allowable value of chamfer dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This outer ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381435
Inside diameter	32 mm
Outside diameter	52 mm
Thickness	37 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE