

Needle roller bearing NA4907-U-IKO - NA4907-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na4907-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
35	—	NA 4907U	—	—	179	35	55	20	21

r _s min (¹)	F _w	Standard mounting dimensions mm				Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		Min.	Max.	d _s	D _s Max.			
0.6	42	39	41	51	30 100	46 300	4 500	LRTZ 354221

Note⁽¹⁾ Minimum allowable value of chamfer dimension r
 Note⁽²⁾ Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381466
Inside diameter	35 mm
Outside diameter	55 mm
Thickness	21 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE