

## Needle roller bearing NA6907-U-IKO - NA6907-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na6907-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
<b>35</b>	—	—	—	—	<b>NA 6907U</b>	<b>320</b>	<b>35</b>	<b>55</b>	<b>36</b>	<b>37</b>

r <sub>s</sub> min (1)	F <sub>w</sub>	Standard mounting dimensions mm		Basic static load rating C <sub>0</sub> N	Basic dynamic load rating C <sub>10</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		Min.	Max.					
0.6	42	39	41	51	51 600	92 600	4 500	LRTZ 354237

Note(1) Minimum allowable value of chamfer dimension r  
 (2) Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381473
Inside diameter	35 mm
Outside diameter	55 mm
Thickness	37 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE