

## Needle roller bearing NA6908-U-IKO - NA6908-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na6908-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
<b>40</b>	—	—	—	—	<b>NA 6908U</b>	<b>440</b>	<b>40</b>	<b>62</b>	<b>40</b>	<b>41</b>

$r_s$ mm	$F_w$	Standard mounting dimensions mm			Basic static load rating $C_0$	Basic dynamic load rating $C$	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		Min.	Max.	$d_s$				
<b>0.6</b>	<b>48</b>	<b>44</b>	<b>47</b>	<b>58</b>	<b>63 700</b>	<b>117 000</b>	<b>4 000</b>	<b>LRTZ 404841</b>

Note(1) Minimum allowable value of chamfer dimension r  
 (2) Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381510
Inside diameter	40 mm
Outside diameter	62 mm
Thickness	41 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE