

Needle roller bearing NA4909-U-IKO - NA4909-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na4909-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|------------------|-----------------------|---------------|----------------|---------------|---------------------|---------------------------|----|----|----|
| | With two seals | With one seal | With two seals | With one seal | | d | D | C | B |
| 45 | — | NA 4909U | — | — | 290 | 45 | 68 | 22 | 23 |

| r _s min ⁽¹⁾ | F _w | Standard mounting dimensions mm | | | | Basic static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring |
|-----------------------------------|----------------|------------------------------------|------|------|--------|---|--|----------------------|
| | | Min. | Max. | Min. | Max. | | | |
| 0.6 | 52 | 49 | 51 | 64 | 38 900 | 63 400 | 3 500 | LRTZ 455223 |

Note(1) Minimum allowable value of chamfer dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952381541 |
| Inside diameter | 45 mm |
| Outside diameter | 68 mm |
| Thickness | 23 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE